

# PRO FORM

## FILM FACED PLYWOOD

Pro Form Film Faced Plywood can be used approximately 8-12 times which is best for the market that requires strict quality while having to maintain the most competitive pricing. With 100% grade core A and % WBP Melamine up to 18%. When using formwork, it helps save cost and time.

- Specialized for concrete formwork
- Good concrete surface
- 8-12 times uses

### **Brand**

PCV THUAN PHAT

### **Standard sizes**

1220x2440mm, 1250x2500mm, cut to size as buyer's request

Tolerant: +/- 0.5mm per meter

### **Standard thickness**

12mm,15mm,17mm,18mm,

as buyer's request

Thickness tolerant: +/- 0.2mm - 0.5 mm

### **Surface**

Phenolic Surface Film (PSF) on both side, back/brown color

Logo: PCV THUAN PHAT or as buyer's request

### **Core veneer**

Hardwood: Acacia/Eucalyptus/Combine

### **Glue**

Melamine/Phenol

### **Formaldehyde Emission Standard**

E0/E1/E2

### **Moisture Content**

<12% (less than twelve percent)

### **Wood material**

Legally Source Plantation Wood

### **Origin**

Vietnam

**Pouring Number**

Pro Form FFP is designed for use from 8-12 times

**Edge color**

Black, Red, Brown, as buyer's request

**Density**

610-625kg/m<sup>3</sup>

**Packaging**

Panels are packed in crates with metal straps then put into container by forklifts.

<b>Thickness</b>	<b>Crate per container</b>	<b>Panel per Crate</b>	<b>Cubic meter per container</b>
12mm	16	82	40-46
15mm	16	65	
17mm	16	58	
18mm	16	55	

\*\*\*This is standard container packaging for international shipping for your reference.

**PCV THUAN PHAT GROUP VIETNAM****Headquarter**

Sales Department

Head Office/Factory: Nghia Lo Village, Chi Dao Ward, Van Lam District, Hung Yen Province, Viet Nam.

Mobile: (whatsapp/skype/ viber): 84-868914282

Email: [phungthanhvan2021@gmail.com](mailto:phungthanhvan2021@gmail.com)